



MODEL: E50XN

All trucks shown with optional equipment. Please refer to quotation specifications.

CUSTOMER DETAILS

| | | | |
|------------------------|--|---------------------------|--|
| CUSTOMER | Whitestown Wastewater Treatment Plant | | |
| ADDRESS | 7728 S CR 450 E, Brownsburg, Indiana, 46112 | | |
| SHIP-TO ADDRESS | 7728 S CR 450 E, Brownsburg, Indiana, 46112 | | |
| CONTACT NAME | Daniel Lockhart | Wastewater Superintendent | |
| PHONE | (317) 295-6346 | | |

| | | | |
|---------------------|-----------------------------|-------------------------|------------------------------|
| PROPOSED BY | Casey Lowry | TITLE | Material Handling Specialist |
| PHONE / CELL | 309-579-8020 / 317-432-4260 | EMAIL | clowry@mhequipment.com |
| DATE | Jan 18, 2022 | QUOTE EXPIRATION | Feb 18, 2022 |



Quoted Model: E50XN Available Features

Hyster® E50XN lift truck. 5,000 lb. nominal capacity at a 24" load center. Hyster® counterbalanced sit-down electric rider lift trucks feature quality and dependability, incorporating proven design processes and systems to ensure the toughest, most durable lift trucks available. These trucks feature low operating costs, superior ergonomics, great dependability and exceptional productivity. With maximized visibility, smooth, precise mast positioning, low-effort steering, and "human-engineered" operating controls, everything about these forklift trucks makes them easy to operate. The rear-opening, one-piece steel hood and the onboard diagnostics are designed with serviceability in mind. Outstanding component access makes servicing fast, easy and convenient. The highly efficient and dependable design of the truck improves battery shift life, saving dollars in energy costs, as well as increasing productivity through improved uptime. Standard features include: AC Traction and Pump Motors, Transistor Drive and Pump Control, Advanced Vehicle System Manager (VSM), Progressive Thermal Management System, Fully Integrated CANbus Communication, On-Demand Power Steering, Hyster® Stability System (HSS), Power Assist Braking, Auto Deceleration System (ADS) with Regenerative Braking, Electronic Horn, Static Strap and Tow Pin. Truck Status is communicated to the operator with a Multi-Functional Display which provides Battery State of Charge, Low Battery Lift Interrupt, Hour Meters, Performance Mode Indicators, Fault Indicator, and 4 Operator Selectable, Programmable Performance Modes. Operator comfort and productivity is enhanced with an Operator Convenience Station containing multiple Storage Areas, Beverage and Clipboard Holders, Infinitely Adjustable Tilt Steering Column, No-Cinch Operator Restraint System, Cushioned Floormat, Contoured Ingress / Egress Handle, Seat Side Power Disconnect Button and Operator Presence System (OPS).

Proposal Summary

| Included Items | Description | Quantity |
|-------------------------|---|----------|
| Model | Hyster® E50XN - Counterbalanced Sit-Down Electric Rider Lift Truck - 5,000 lb. Nominal Capacity @ 24" Load Center | 1 |
| Construction | Standard Performance Standard Construction - Operating Temperatures +32° F to +120° F Key Switch Start UL Classification Type "E" 36 Volt | |
| Battery Compartment | Battery Charging System - Conventional - Includes Single Battery Connector Under the Hood Battery Compartment - 27.6" Long x 39.1" Wide x 23.9" High (700mm x 992mm x 607mm) Battery Removal without Rollers - Lift Out | |
| Mast | 3-Stage Full Free Lift Mast, 189" Maximum Lift Height Mast Tilt - 5° Forward / 5° Back | |
| Carriages & Attachments | 38.5" (977mm) Wide - Class II - Hook Type Integral Sideshifting Fork Positioner Carriage 48" (1220mm) High Load Backrest Extension | |
| Forks | 42" Long x 1.6" Thick x 3.9" Wide (1067mm x 40mm x 100mm) - Class II Hook Type - Standard Taper Forks | |
| Hydraulics | 4 Function (2 Auxiliary) Hydraulic Control Valve Mechanical Lever Hydraulic Controls - Seat Side | |
| Hoses | 2 Auxiliary Function Hose Group - 4 Hoses Internally Mounted | |
| Wheels & Tires | Drive Tires - 21 x 7 x 15 - Cushion - Standard Compound - Lug Tread - Standard Tread Width - 42.1" (1070mm) Over All Width Steer Tires - 16 x 5 x 10.5 - Cushion - Standard Compound - Smooth Tread | |



| | |
|-------------------------------|---|
| Operator Compartment | Display - High Mount - Mounted in Upper Right Corner of Overhead Guard Rear Drive Handle with Horn Button 84.1" (2137mm) Overhead Guard - Flat Plate |
| Directional Control | MONOTROL® Directional Control Pedal Park Brake - Manual - Foot Applied / Hand Released Tilt Steering Column - Infinitely Adjustable within a 26 Degree Range - Gas-Spring Assisted On Demand Hydrostatic Power Assist Steering Steering Wheel with Spinner Knob |
| Seat | Seat Belt - Black - No-Cinch with ELR (Emergency Locking Retractor) Non-Suspension Vinyl Seat |
| Lights & Alarms | Audible Alarm - Reverse Direction Activated - Factory Set to 87 dB(A) - Manually Adjustable to 87, 97 or 102 dB(A) Work Lights - LED Plastic Lens - 2 Front and 1 Rear DC to DC Converter - Primary - For Factory Installed Options - 25 amps/300 watts @ 12 volts |
| Warranty | 12 Months / 2,000 Hours Manufacturer's Warranty, 36 Months/ 6,000 Hours Manufacturer's Powertrain Warranty |
| Literature & Nameplate | English Literature Pack and Labels |
| Battery & Charger Accessories | Battery Connector - Grey SB® 350 Lead Acid Battery Power -- Truck Configured to Operate on Lead Acid Battery Power |

Additional Items or Accessories Included

| | Description | Quantity |
|---------|--|----------|
| Battery | 18-90-23 Industrial Battery with Single Point Watering System and Smart Blinky | 1 |
| Charger | Industrial Charger, 3 Phase | 1 |
| Freight | Freight to Customer | 1 |

Total Investment

| | | | |
|------------------------|-------------|---------------|-------------|
| Price E50XN | \$44,150.00 | Qty: 1 | |
| Quoted Quantity | 1 | TOTAL: | \$44,150.00 |

TERMS: NET 10 DAYS UNLESS OTHERWISE SPECIFIED Accounts past due are subject to a 1.5 percent service charge (annual rate 18 percent) and all costs of collection including reasonable attorneys fees. If a credit card is used for payment a 3 percent convenience fee will be assessed. Other acceptable methods of payment are check or wire transfer. Pricing in this proposal does not include Sales Tax. Sales Tax, as applicable, will be calculated and added in accordance with State Law. Tax exempt transactions require the appropriate Tax Exempt certificate to be on file with MH Equipment. Thank you again for the opportunity to address your material handling requirements. We are committed to delivering a comprehensive, competitive material handling solution for your operations needs, and will work diligently with you to address your costs through increased productivity and maximized efficiencies. Please advise how we can be of further assistance.

| | | | |
|---------------------|-------------|-----------------------|-------|
| Proposal By: | Casey Lowry | Accepted By: | |
| Signature: | <hr/> | Signature: | <hr/> |
| Date Signed: | <hr/> | Date Accepted: | <hr/> |
| | | PO Number: | <hr/> |